



KONICA MINOLTA

**bizhub
i-SERIES IS
SMARTER
WORKING**
RETHINK IT



bizhub C750i
Color A3 multifunctional

CLOUD ENABLED



Giving Shape to Ideas

CUSTOMER BENEFITS



Intuitive operability
Operate the bizhub like a smartphone or tablet with fully customizable user interface



Mobile connectivity
Print anytime from anywhere with Konica Minolta's innovative mobile technologies



Security
Secure network integration, data encryption, and advanced user authentication



Application ecosystem
Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



Productivity
Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability
Numerous eco features reduce energy consumption and costs

OPTIONS

1 ENHANCED FEATURES

- Barcode fonts
LK-106
- Unicode fonts
LK-107
- OCR A and B fonts
LK-108
- Document converter pack
LK-110v2
- ThinPrint® client
LK-111
- Antivirus
LK-116
- IP fax (T.38 fax)
LK-117 (TBD)



2 CONNECTIVITY

- Fax board
FK-514 x2
- Wireless LAN
UK-221
- USB I / F kit
EK-608
- USB I / F kit
EK-609 OR
- Fiery controller
IC-420
- Interface kit for IC-420
VI-516
- Biometric authentication
AU-102
- ID card reader
AU-205H OR
- Mount kit
MK-735

3 OTHERS

- Working table
WT-506
- Upright panel
WT-519
- 10-Key pad
KP-102
- Security kit
SC-509
- 1 TB SSD
EM-908
- Keyboard holder
KH-102
- External Keyboard

4 MEDIA INPUT

- Large capacity tray
LU-303 OR
- Large capacity tray
LU-205
- Banner tray
MK-730

5 MEDIA OUTPUT

- Output tray
OT-514 OR
- Staple finisher
FS-539 OR
- Relay unit
RU-519 OR
- Booklet finisher
FS-539SD OR
- Relay unit
RU-519 OR
- Punch kit for FS-539/SD
PK-524 OR
- Staple finisher
FS-540 OR
- Relay unit
RU-519 OR
- Booklet finisher
FS-540SD OR
- Relay unit
RU-519 OR
- Punch kit for FS-540/SD
PK-526 OR
- Post inserter for FS-540/SD
PI-507 OR
- Job separator for FS-540/SD
JS-602 OR
- Z-fold unit for FS-540/SD
ZU-609

LEGEND

- Mandatory option
- Option
- This option can only be installed with the respective option above it

*Not available at time of launch

FINISHING FUNCTIONALITIES



Corner stapling



Two-point stapling



Two-hole punching



Three-hole punching



Duplex



Combined mixplex/mixmedia



Half-fold



Sheet insertion



Tri-fold



Booklet



Offset sorting



Z-fold



Banner printing



Corner Stapling (offline)

DESCRIPTION

ENHANCED FEATURES

| | |
|----------------------------------|---|
| LK-106 Barcode fonts | Supports native barcode printing |
| LK-107 Unicode fonts | Supports native Unicode printing |
| LK-108 OCR A and B fonts | Supports native OCR A and B font printing |
| LK-110v2 Document converter pack | Supports Searchable PDF, PDF encryption, PDF/A, linearized PDF file formats, and generates OOXML (DOCX, XLSX, etc.) file formats. |
| LK-111 ThinPrint® client | Print data compression for reduced network impact |
| LK-116 Antivirus | Bitdefender® antivirus provides real time scanning of all incoming and outgoing data |
| LK-117 FOIP activation (TBD) | Fax over IP networks (T.38), requires fax kit |

CONNECTIVITY

| | |
|---------------------------------|---|
| FK-514 Fax board | Super G3 fax, digital fax functionality |
| UK-221 Wireless LAN | Wireless LAN and wireless LAN Access Point Mode |
| EK-608 USB I/F kit | USB keyboard connection |
| EK-609 USB I/F kit | USB keyboard connection; Bluetooth |
| IC-420 Fiery controller | Professional color print controller |
| VI-516 Interface kit for IC-420 | Fiery controller interface card |
| AU-102 Biometric authentication | Finger vein scanner |
| AU-205H ID card reader | Various ID card technologies |
| MK-735 Mount kit | Installation kit for ID card reader |

OTHERS

| | |
|------------------------|--|
| WT-506 Working table | Authentication device placement |
| WT-519 Working table | Working table for upright panel |
| KP-102 10-Key pad | For numeric entry instead of touchscreen |
| SC-509 Security kit | Copy guard function |
| EM-908 1 TB SSD | 1 TB SSD to increase storage space |
| KH-102 Keyboard holder | To place USB keyboard |
| External Keyboard | Keyboard for alpha numeric data entry |

MEDIA INPUT

| | |
|----------------------------|---|
| LU-303 Large capacity tray | 3,000 sheets, 8.5" x 11"; 52–256 g/m ² |
| LU-205 Large capacity tray | 2,500 sheets, 8.5" x 11" - 12" x 18"; 52–256 g/m ² |
| MK-730 Banner tray | Multipage banner feeding |

MEDIA OUTPUT

| | |
|------------------------------------|---|
| OT-514 Output tray | Output tray used instead of finisher |
| FS-539 Staple finisher | 50-sheet stapling; 3,200 sheets max. output |
| FS-539SD Booklet finisher | 50-sheet stapling; 20-sheet booklet finisher; 2,200 sheets max. output |
| PK-524 Punch kit for FS-539/SD | 2/3 hole punching; autoswitching |
| FS-540 Staple finisher | 100-sheet stapling; 3,200 sheets max. output |
| FS-540SD Booklet finisher | 100-sheet stapling; 20-sheet booklet finisher; 2,700 sheets max. output |
| PK-526 Punch kit for FS-540/SD | 2/3 hole punching; auto switching |
| RU-519 Relay unit | For FS-539/SD or FS-540/SD installation |
| PI-507 Post inserter for FS-540/SD | Cover insertion; post finishing |
| JS-602 Job separator for FS-540/SD | Separation of fax output; etc. |
| ZU-609 Z-fold unit for FS-540/SD | Z-fold for 11" x 17" prints |

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

| | |
|--------------------------------|--|
| System speed letter | Up to 75/70 ppm (mono/color) |
| System speed 11" x 17" | Up to 37/35 ppm (mono/color) |
| Auto duplex speed letter | Up to 75/70 ppm (mono/color) |
| 1st page out time letter | 2.8/3.8 sec. (mono/color) |
| Warm-up time | Approx. 17/18 sec. (mono/color) ¹ |
| Imaging technology | Laser |
| Toner technology | Simitri® HD polymerized toner |
| Panel size/resolution | 10.1" / 1024 x 600 |
| System memory | 8,192 MB (standard/max) |
| Solid state drive | 256 GB SSD (standard) / 1 TB SSD (optional) |
| Interface | 10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n/ac (optional) |
| Network protocols | TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour |
| Automatic document feeder | Up to 300 originals; 4.13" x 5.83" - 11" x 17"; 35–210 g/m ² ; Dual scan ADF |
| ADF double feed detection | Standard |
| Printable paper size | 3.5" x 5.5" - 12" x 18"; custom paper sizes, banner paper max. 47.2" x 11.7" |
| Printable paper weight | 52–300 g/m ² |
| Paper input capacity | 3,650 sheets / 6,650 sheets (standard/max) |
| Paper tray input (standard) | 1x 500; 3.5" x 5.5" - 11" x 17"; custom sizes; 52–256 g/m ² 1x 500; 5.5" x 8.5" - 12" x 18"; custom sizes; 52–256 g/m ² 1x 1,500; 5.5" x 8.5" - 8.5" x 11"; 52–256 g/m ² 1x 1,000; 5.5" x 8.5" - 8.5" x 11"; 52–256 g/m ² |
| Large capacity tray (optional) | 1x 3,000; 8.5" x 11"; 52–256 g/m ² 1x 2,500; 8.5" x 11" - 12" x 18"; custom sizes; 52–256 g/m ² |
| Manual bypass | 150 sheets; 3.5" x 5.5" - 12" x 18"; custom sizes; banner; 60–300 g/m ² |

SYSTEM SPECIFICATIONS

| | |
|------------------------------|--|
| Finishing modes (optional) | Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold; Letter-fold; Booklet; Post insertion; Z-fold |
| Automatic duplexing | 3.5" x 5.5" - 12" x 18"; 52–256 g/m ² |
| Output capacity | Up to 200 sheets / up to 3,300 sheets (standard/max) |
| Stapling | Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m ²) |
| Stapling output capacity | Max. 200 sets |
| Letter fold | Max. 3 sheets |
| Letter fold capacity | Max. 50 sets; unlimited (without tray) |
| Booklet | Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m ²) |
| Booklet output capacity | Max. 35 booklets; unlimited (without tray) |
| Duty cycle (monthly) | Max. ² 300,000 pages |
| Toner lifetime | Black up to 45,000 pages CMY up to 45,000 pages |
| Imaging unit lifetime | Black up to 240,000/1,000,000 pages (drum/developer) CMY up to 165,000/1,000,000 pages (drum/developer) |
| Power consumption | 110-120V/ 50/60 Hz; Less than 2.10 kW |
| System dimension (W x D x H) | 24.2" x 27.1" x 47.5" (without options) |
| System weight | Approx. 353 lbs. (without options) |

PRINTER SPECIFICATIONS

| | |
|---------------------------|--|
| Print resolution | 1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi |
| Page description language | PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS |
| Operating systems | Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.11 or later; Unix; Linux; Citrix |
| Printer fonts | 80 PCL Latin; 137 PostScript 3 Emulation Latin |

PRINTER SPECIFICATIONS

| | |
|------------------------|---|
| Mobile printing | AirPrint (iOS); Mopria (Android); Konica Minolta Print Service (Android); Konica Minolta Mobile Print (iOS/Android) Optional: Wi-Fi Direct |
|------------------------|---|

PRINTER SPECIFICATIONS (OPTIONAL)

| | |
|----------------------------------|--|
| Print controller | Embedded Fiery IC-420 |
| Controller CPU | AMD GX-424CC @ 2.4 GHz |
| Memory/HDD | 4,096 MB / 500 GB |
| Page description language | Adobe PostScript 3 (CPSI 3020); PCL 6; PCL 5c |
| Operating systems | Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.11 or later; Linux |

SCANNER SPECIFICATIONS

| | |
|--------------------------|--|
| Scan speed | Up to 140/140 ipm in simplex (mono/color) Up to 280/280 ipm in duplex (mono/color) |
| Scan resolution | Up to 600 x 600 dpi |
| Scan modes | Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL; TWAIN scan |
| File formats | JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS; PPTX; PDF/A 1a and 1b optional: Searchable PDF; Searchable DOCX/PPTX/XLSX |
| Scan destinations | 2,000 destinations + 100 groups; LDAP support |

COPIER SPECIFICATIONS

| | |
|------------------------|----------------------------------|
| Copy resolution | 600 x 600 dpi |
| Gradation | 256 gradations |
| Multicopy | 1-9,999 |
| Original format | Max. 11" x 17" |
| Magnification | 25-400% in 0.1% steps; Auto-zoom |

FAX SPECIFICATION

| | |
|-------------------------|------------------------------------|
| Fax standard | Super G3 (optional) |
| Fax transmission | Analog; i-Fax; Color i-Fax; IP-Fax |
| Fax resolution | Up to 600 x 600 dpi |
| Fax compression | MH; MR; MMR; JBIG |
| Fax modem | Up to 33.6 Kbps |
| Fax destinations | 2,000 single + 100 groups |

USER BOX SPECIFICATIONS

| | |
|---------------------------|--|
| Storable documents | Up to 3,000 documents or 10,000 pages |
| User boxes | Public; Personal (with password or authentication); Group (with authentication) |
| System boxes | Secure print; Encrypted PDF print; Fax receipt; Fax polling |

SYSTEM FEATURES

| | |
|-------------------------------------|---|
| Security | ISO 15408 HCD-PP Common Criteria (in evaluation); IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support; IEEE 802.1x support; User authentication; Authentication log; Secure print; Kerberos; Overwrite all data function; SSD self-encryption (AES 256)/Storage lock password; Confidential fax; Print user data encryption |
| Security function (optional) | Antivirus realtime scanning (Bitdefender®); Copy protection (Copy Guard; Password Copy) |
| Accounting | Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder); User function access definition; Authentication by mobile device (Android) optional: Biometric authentication (finger vein scanner); ID card authentication (ID card reader); Authentication by mobile device (iOS) |
| Software | Net Care Device Manager; Data Administrator; Web Connection; Log Management Utility |

¹ Warm-up time may vary depending on the operating environment and usage

² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to 8.5" x 11"-size paper of 80 g/m² quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

Simitri HD
High Definition Polymerized Toner

SAP® Printer Vendor
Solution



For complete information on Konica Minolta products and solutions,
please visit: [CountOnKonicaMinolta.com](https://www.CountOnKonicaMinolta.com)

© 2023 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.
100 Williams Drive, Ramsey, New Jersey 07446

[CountOnKonicaMinolta.com](https://www.CountOnKonicaMinolta.com)



Item #: C750iSS
10/2023-Z